

# EUROSAFE

## QUICK COUPLER



HYDRAULIC



MECHANICAL

EUROSAFE Quick Coupler (Hydraulic version)  
Quick coupler that fits every type of bucket and OE item, without editing requirements.

- Easy to install on excavator.
- Allow the replace of different equipment, on the excavator, in a short time.
- Completely safe, thanking the safety pin, the lock valve (hydraulic version) and the lock safety screw (mechanical version).
- Its special structure allows to recover immediately the lacks coming from the wear process during its lifetime.

- Almost every model allows to also a reversible use of the bucket.
- Convertible from mechanical to hydraulic with a special kit (apart).
- Completely safe: in compliance with the UNI 474-1 norm.

- universal: compatible with many attachment and buckets
- compact
- reversible: allows to set the bucket in reverse position
- safe: safety system to avoid unexpected unhooking
- hydraulic or mechanical version available
- wide range of pins interacts

### EUROSAFE MINI HYDRAULIC version

MODEL	CODE	PINS	PINS INTERAXIAL min/max	PINS INTERAXIAL range
EURO SAFE 40 only for dipper width over 150	10Z040	40	170>204 205>239 240>274 275>309 310>350	34
EURO SAFE 45 only for dipper width over 160	10Z045	45	220>254 255>289 290>324 325>359 360>400	34
EURO SAFE 50	10Z050	50	235>269 270>304 305>339 340>380	34
EURO SAFE 55	10Z055	55	275>315	40

## EUROSAFE HYDRAULIC version

MODEL	CODE	PINS	PINS INTERAXIAL min/max	PINS INTERAXIAL range
EURO SAFE 60	10Z060	60	330>380 380>430	50 50
EURO SAFE 65	10Z065	65	355>394 395>445	39 50
EURO SAFE 70	10Z070	70	370>429 430>500	59 70
EURO SAFE 80	10Z080	80	400>459 460>530	59 70
EURO SAFE 90	10Z090	90	460>514 515>580	54 65
EURO SAFE 100	10Z100	100	500>559 560>630	59 70
EURO SAFE 110	10Z110	110	535>600	65
EURO SAFE 120	10Z120	120	580>645	65

10

## EUROSAFE MINI MECHANICAL version

MODEL	CODE	PINS	PINS INTERAXIAL min/max	PINS INTERAXIAL range
EURO SAFE 40 only for dipper width over 150	10W040	40	170>204 205>239 240>274 275>309 310>350	34
EURO SAFE 45 only for dipper width over 160	10W045	45	220>254 255>289 290>324 325>359 360>400	34
EURO SAFE 50	10W050	50	235>269 270>304 305>339 340>380	34
EURO SAFE 55	10W055	55	275>315	40

## EUROSAFE MECHANICAL version

MODEL	CODE	PINS	PINS INTERAXIAL min/max	PINS INTERAXIAL range
EURO SAFE 60	10W060	60	330>380 380>430	50 50
EURO SAFE 65	10W065	65	355>394 395>445	39 50
EURO SAFE 70	10W070	70	370>429 430>500	59 70
EURO SAFE 80	10W080	80	400>459 460>530	59 70
EURO SAFE 90	10W090	90	460>514 515>580	54 65