



Performance in every detail

PRODUCT OVERVIEW

Keestrack N.V. Taunusweg 2 3740 Bilzen Belgium

T +32 (0)89 515851 info@keestrack.net

www.keestrack.com

Follow us on 🕡 🗓 💿







The joy <mark>of working</mark>



Working with the right tools motivates people and ensures a top performance. With Keestrack Equipment you always have the right tools in place.

Keestrack mobile crushing and screening equipment do not only do a good job, they also make your life easier. Simple to operate and to maintain and very cost effective. Available with loads of options to facilitate your job at hand.

Have fun at work, work harder with Keestrack!



History



Since 1988 Keestrack designs and produces mobile screening and crushing equipment in-house. The complete production process is privately owned.

Quality, innovation, flexibility and after sales support play a central role and Research and Development ensures Keestrack stays ahead of competition.

Keestrack was the first with direct feed screens and even today, competition cannot match the results. The original patented Keestrack concept is today's industry standard!

After developing a range of screens and classifiers Keestrack developed the mobile impact crushers.

After the acquisition of OM in 2010, Keestrack added a complete range of jaw crushers to its product range.


Currently Keestrack has a wide range of:

- mobile screens and classifiers
- mobile impact crushers
- mobile jaw crushers
- mobile cone crushers
- mobile stackers
- dust suppression Cannon
- mobile drum screens

Nowadays Keestrack is a global player with a dealer network with knowledgeable and service minded partners.



Designed to simplicity



The goal of Keestrack is to make products as user friendly as possible by using today's technology.

Keestrack products are easy to operate, maintain, and to access for replacing wear and spare parts.

Design is focused on productivity, safety and ease of use.

Keestrack uses technology to have the lowest possible costs per produced ton.

Energy consumption plays an important role in the costs that is why Keestrack offers both hydraulic electric and hybrid systems.

All equipment is track mobile, compact, easy to transport, operational within minutes without support legs and can be used in multiple applications.







Crushers Stackers Screens

| Jaw B-series | Cone H-series | Impact R-series | Scalper K-series | Classifiers C-series | Drum D-series | Stacker S-series |
|-----------------|------------------|--------------------|-----------------------|--------------------------|--------------------------|-----------------------|
| | | | k 2 | | | Sz 👝 |
| | | | (Top Soil) | | | (Feeder/Sorting belt) |
| Вз | | R3 | K3 | C ₃ | | Sz |
| (Argo) | | (Destroyer 1011) | (Combo) | (Explorer 1200 3-D) | | (Stacker 08-18) |
| B ₄ | Н4 | | K ₄ | C_4 | \Box_{4} | |
| (Apollo) | е | | (Novum) | (Explorer 1500 3-D) | (414) | |
| B ₅ | | R5 | K 5 | | D ₅ w&T | S ₅ |
| (Giove) | | (Destroyer 1113) | (S175) | | (518) | (Stacker 10-23) 🧲 |
| B6 | | R6 e | К е | CO _ | D6 | |
| (Saturno) | | (Destroyer 1313) | (Frontier) | (Explorer 1800 2-D; 3-D) | ₍₆₂₀₎ W&T | |
| | | | K | | D _w | |
| | | | (НР) | | (720) | |
| | | | K8 | Co | W= wheeled T= Tracked | |
| | | | (Giant) | (Giant 2-D; 3-D) | I – II dCREU | |

Compatibility

Capacity

5

Product Matrix

Keestrack's product matrix has been set up to give an overview of the mobile solutions Keestrack offers.

The colums show the different products, the higher the number the more throughput capacity of the equipment.

The lines show which machines fit together in a production line.

Another unique feature of Keestrack.

6

Drive systems

All Keestrack equipment can be configured to suit your application. Options to make your life easier and to save money, or better, to make money!

Your choice of drive

As fuel and energy costs are getting an increasing effect on operational costs Keestrack offers several drive systems.

Fuel Saving Load sensing technology
Keestrack's basic version is an advanced
Diesel engine with low emission norms
combined with a load sensing hydraulic system
which ensures a minimum impact on the
environment.

Load sensing hydraulic save 4 to 6 l of Diesel fuel an hour.

Electric, energy saving, plug-in version C
The Diesel/Electric powered equipment can operate:

- autonomous to the Diesel powered generator (genset),
- by connecting to electrical mains *
- by connecting to an external generator *.

Operating results are of the same high quality as the basic Diesel hydraulic model however maintenance and operating costs are considerable lower.

* R5 & R6 are available in Electric version with direct driven Rotor by Diesel engine

After Sales Service

Servicing your equipment is important and Keestrack and its dealers offer support by delivering wear and spare parts, offering maintenance and repair on site or in our workshops.









Screens





K



- Belt feeder
- Double deck screen box 2.700 x 1.200 mm (9' x 4')
- 1 Protection deck
- 1 Screen deck
- 2 Split screening
- 3,24 m² screening surface
- Capacity up to 150 tonnes / hour
- Feed hopper 5 m³
- Deutz 55 kW, low emission engine



- Top soil and many other products
- Pre-screening/scalping
 - Separation of "sticky" material
 - Screening behind or before a crusher
 - Sand, gravel and others

| | Transport Dimensions | Working Dimensions |
|--------|----------------------|---------------------|
| Weight | 14 t (15,8 sT) | |
| Length | 9.930 mm (32'7") | max. 9970 mm (32'8) |
| Height | 3.090 mm (10'2") | 3.300 mm (10'10") |
| Width | 2.600 mm (8'6") | 6.400 mm (21'0") |

Quick overview

| Screens & classifiers | K2 | К3 | K4 | K5 | K6 | K7 | K8 | C3 | C4 | C6 | C8 |
|-----------------------|------|------|-----|-----|-----|------|------|-----|-----|-----|------|
| Capacity (t/h) | 150 | 250 | 350 | 450 | 600 | 1000 | 1200 | 200 | 400 | 400 | 600 |
| Upper deck m² | 3,24 | 3,24 | 6,3 | 7,5 | 8,1 | 8,7 | 12 | 4,3 | 5,4 | 8,1 | 11,4 |
| Middle deck m² | • | • | • | • | • | • | • | 4,3 | 5,4 | 8,1 | • |
| Lower deck m² | 3,24 | 3,24 | 5,4 | 6,6 | 8,1 | 8,7 | 12 | 3,4 | 5,4 | 8,1 | 11,4 |
| Standard hopper m³) | 5 | 6 | 7 | 7 | 8 | 8 | 12 | 5 | 8 | 8 | 12 |

| Drum screens | D4 | D5 | D6 | D7 | |
|---------------------------------------|-------------|-------------|-------------|-------------|--|
| Drum dimensions length, diameter (mm) | 4400 / 1400 | 4700 / 1800 | 5500 / 2000 | 7200 / 2000 | |
| Hopper (m³) | 3 | 5 | 5 | 6 | |

| Impact crushers | R3 | R5 | R6 | |
|---------------------------|-----------------------------|-----------------------------------|-----------------------------------|--|
| Capacity (t/h) | 250 | 350 | 500 | |
| Inlet opening H x W (mm) | 770 x 960 | 800 x 1050 | 900 x 1280 | |
| Rotor diameter/width (mm) | 1093 / 920 | 1260 / 1000 | 1267 / 1250 | |
| Pre screen (mm) | punched plate 1200 x 920 | independent 2 deck 2200 x 1000 | independent 2 deck 3100 x 1250 | |
| After screen (mm) | single deck 2800 x 1200 | single deck 3300 x 1500 | double deck 4500 x 1500 | |
| Standard hopper (m³) | 3,5 | 5 | 7 | |
| Dolly system | • | 4-axle, wheeled | 4-axle, wheeled | |

| Jaw Crushers | В3 | B4 | B5 | В6 |
|----------------------|---|--------------------------------------|--------------------------------------|---|
| Capacity (t/h) | 300 | 400 | 420 | 450 |
| Feed size (mm) | 500 | 600 | 650 | 800 |
| Feed opening (mm) | 1000 - 600 | 1100 - 700 | 1100 - 800 | 1100 - 900 |
| C.S.S. min max. (mm) | 45 - 170 | 45 - 160 | 70 - 175 | 100 - 210 |
| Pre screen (mm) | vibrating feeder grizzly 1450 x 920 | independent 2 deck 2300 x 1000 | independent 2 deck 2300 x 1000 | vibrating feeder 2 step grizzly 2200 x 1080 |
| Standard hopper (m³) | 4 | 5 | 5 | 6 |

| Cone Crusher | H4 | |
|----------------------------|-----------------------|--|
| Capacity (t/h) | 250 | |
| Feed size (mm) | 185 | |
| C.S.S. min max. (mm) | 6 - 38 | |
| Pre screen (mm) optional | 1200 x 1800 | |
| After screen (mm) optional | 3 deck 3600 x 1500 mm | |
| Standard hopper (m³) | 8 | |



| Stackers | S2 | S3 | S 5 | |
|------------------------|--------------|---------------|---------------|--|
| Capacity (t/h) | 500 | 250 | 500 | |
| Feed size (mm) | 200 | 200 | 200 | |
| Stockpile capacity (t) | 390 | 1200 - 7500 | 2500 - 15000 | |
| Manual sorting station | left & right | • | • | |
| Standard hopper (m³) | 3,5 | feeding chute | feeding chute | |

Social Media







https://www.facebook.com/Keestrack

https://www.linkedin.com/company/keestrack

https://twitter.com/keestrack1

http://vimeopro.com/keestrack/crushingandscreeningequipment

https://www.youtube.com/user/MrKeestrack

Sales Offices

Keestrack NV

Taunusweg 2

3740 Bilzen

Belgium

SPARE PARTS - Belgium

Spareparts & Service Offices

tel: +32 89 515 861 fax: +32 89 515 848

mobile: +32 491 712 215 email:spares@keestrack.net

phone: +32 (0)89 515851 info@keestrack.net

Keestrack-OM SPA

SPARE PARTS - Italy tel: + 39 0422 441311 fax: + 39 0422 441421

email:spares@keestrack.it

Via postumia, 62 31050 Ponzano Veneto (Treviso)

Italy

phone: +39 0422 441311 keestrack@keestrack.it

SPARE PARTS - Czech Republic

tel. +420 585 001 327 fax. +420 585 001 327 mobil: +420 724 093 942 email:spares@tridic.com

Chuzhou 239000 China phone: +86 (0) 550 3562505 sales@keestrack-china.com spares@keestrack-china.com

No. 333 North Shanghai Road

SPARE PARTS - U.S.A. tel: 978-452 6400 fax: 978-452 6404

email: keestrackamericaspares@

keestrack.com

A worldwide dealer network

to support customers all over the world!

Keestrack (Chuzhou) Construction Equipment Co., Ltd.









